

Three Phase String Inverter

SUN-60/70/75/80K-G



4 MPP trackers, Max. efficiency up to 98.7%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)



Type II DC/AC SPD

Deye

Stock Code: 605117.SH

| Model | SUN-60K-G | SUN-70K-G | SUN-75K-G | SUN-80K-G |
|--|---|-------------|-------------|-------------|
| PV String Input Data | | | | |
| Max. PV Input Power (kW) | 78 | 91 | 97.5 | 104 |
| Max. PV Input Voltage (V) | 1000 | | | |
| Start-up Voltage (V) | 250 | | | |
| MPPT Voltage Range (V) | 200-850 | | | |
| Rated PV Input Voltage (V) | 600 | | | |
| Max. Operating PV Input Current (A) | 40+40+40+40 | | | |
| Max. Input Short Circuit Current (A) | 60+60+60+60 | | | |
| No. of MPP Trackers/ No. of Strings per MPP Tracker | 4/3+3+3+3 | 4/4+4+4+4 | | |
| AC Output Side | | | | |
| Rated AC Output Active Power (kW) | 60 | 70 | 75 | 80 |
| Max. AC Output Apparent Power (kVA) | 66 | 77 | 82.5 | 88 |
| Rated AC Output Current (A) | 90.9/87 | 106.1/101.5 | 113.6/108.7 | 121.2/115.9 |
| Max. AC Output Current (A) | 100/95.7 | 116.7/111.6 | 125/119.6 | 133.3/127.5 |
| Rated Output Voltage/Range (V) | 220/380V, 230/400V 0.85Un-1.1Un | | | |
| Grid Connection Form | 3L/N/PE | | | |
| Rated Output Grid Frequency/Range(Hz) | 50/45-55, 60/55-65 | | | |
| Power Factor Adjustment Range | 0.8 leading to 0.8 lagging | | | |
| Total Current Harmonic Distortion THDi | <3% | | | |
| DC Injection Current | <0.5In | | | |
| Efficiency | | | | |
| Max. Efficiency | 98.6% | 98.7% | | |
| Euro Efficiency | 98.0% | 98.1% | | |
| MPPT Efficiency | >99% | | | |
| Equipment Protection | | | | |
| DC Polarity Reverse Connection Protection | Yes | | | |
| AC Output Overcurrent Protection | Yes | | | |
| AC Output Overvoltage Protection | Yes | | | |
| AC Output Short Circuit Protection | Yes | | | |
| Thermal Protection | Yes | | | |
| DC Terminal Insulation Impedance Monitoring | Yes | | | |
| DC Component Monitoring | Yes | | | |
| Ground Fault Current Monitoring | Yes | | | |
| Power Network Monitoring | Yes | | | |
| Island Protection Monitoring | Yes | | | |
| Earth Fault Detection | Yes | | | |
| Overvoltage Load Drop Protection | Yes | | | |
| Residual Current (RCD) Detection | Yes | | | |
| Surge Protection Level | TYPE II(DC), TYPE II(AC) | | | |
| Interface | | | | |
| Communication Interface | RS485/RS232 /WiFi/LAN | | | |
| General Data | | | | |
| Operating Temperature Range (°C) | -25 to +60°C, >45°C Derating | | | |
| Permissible Ambient Humidity | 0-100% | | | |
| Permissible Altitude (m) | 4000m | | | |
| Noise (dB) | ≤50 | ≤55 | | |
| Ingress Protection(IP) Rating | IP 65 | | | |
| Inverter Topology | Non-Isolated | | | |
| Over Voltage Category | OVC II(DC), OVC III(AC) | | | |
| Cabinet Size (WxHxD mm) | 700×575×297 (Excluding Connectors and Brackets) | | | |
| Weight (kg) | 60 | | | |
| Warranty | 5 Years | | | |
| Type of Cooling | Intelligent Air Cooling | | | |
| Grid Regulation | IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, OVE-Richtlinie R25, G99, VDE-AR-N 4105 | | | |
| Safety EMC/Standard | IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2 | | | |